

808VR

Specifications

Camera Specification	1/4" CCD sensor 2.5 Lux / F1.8 (typical); 0.07 Lux / F1.8 (Star light mode) ATW, AGC, AWB, FIX
Lens	10X Optical zoom lens, F= 4.2 ~ 42mm ; Auto Focus, F= 1.8 ~ 2.9mm
Algorithm Supported	MPEG4/MJPEG multi-codec for streaming video ; JPEG for still image
Video Resolution	Resolution: 520 TVL Up to 30 frames at 704*480 (NTSC) ; Up to 25 frames at 704*576 (PAL)
Pan/Tilt/Zoom Range	Support multi-direction movement Pan: Range 355 degree ; Tilt : Range 135 degree 10X Optical zoom, 10X Digital zoom
Physical	10 baseT or 100 baseT Fast Ethernet auto negotiation
Power	Input: 100-240VAC, 50/60Hz, 0.7A ; Output: 12VDC, 1.5A Consumption: Max 12W 802.11af compliant Power over Ethernet (Optional)
System	RAM: 64MB SDRAM ; ROM: 8MB Flash ROM
WLAN (Wireless Model Only)	802.11b/g wireless LAN
Security	WEP/WPA-PSK/WPA2-PSK
Protocol	TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, and RTSP
Features	Adjustable image size, quality and bit rate Time stamp and text overlay ; 4 Motion detection windows
Audio	AMR/G.726 ; Built-in MIC / External MIC input selectable ; Support two-way audio ; Audio output
Operating Environment	Temperature: 0 - 40°C ; Humidity: 85% RH
Dimension	107 x 105 x 110 (mm)
Weight	NET. 425g (Wired Model) ; NET. 455g (Wireless Model)
EMI & Safety	CE, FCC

606VR